

Paso 1 | Configuración de Wifi |

ADC730

ADC FTTH Smartlife ADC730

Status | **Network** | Security | Application | Administration | Maintenance | Help

WAN 中文

Binding Help

LAN Address Setting

Prefix Management

WLAN 2

Basic 3

SSID Settings

Security

Remote Management

QoS

Sntp

Routing

Enable Wireless RF

Mode Mixed(802.11b+802.11g+802.11n) v

Country/Region **United States of America** v Region mas cercana Logout

Band Width 20MHz/40MHz v

Channel **1** v Canal de emision wifi

External Channel Upper v

Sgi Enable

Beacon Interval 100 ms

Tx Rate Auto v

Transmitting Power 100% v

QoS Type WMM v

Choose SSID SSID1 v

Submit Cancel

Paso 2 | Nombre de red Wifi |

ADC FTTH Smartlife ADC730

Status | **Network** | Security | Application | Administration | Maintenance | Help

WAN 中文

Binding Help

LAN Address Setting

Prefix Management

WLAN

Basic

1 SSID Settings

Security

Remote Management

QoS

Sntp

Routing

Choose SSID SSID1 v

Broadcast Disable

SSID Enable

Maximum Clients 32 (1 ~ 32)

2 SSID Name **ADC-rhjp** (1 ~ 32 Char) Nombre de red WIFI

Submit Cancel

Paso 3 | Clave de red Wifi |

ADC730

ADC730

Status | Network | Security | Application | Administration | Maintenance | Help

WAN 中文

Binding Help

LAN Address Setting

Prefix Management

WLAN

- Basic
- SSID Settings
- 1 Security

Remote Management

QoS

SNTP

Routing

Choose SSID

Authentication Type

2 WPA Passphrase (8 ~ 63 characters) Logout

WPA Encryption Algorithm

CLAVE DEL WIFI

Submit Cancel